

Promat



Cafco FENDOLITE[®] MII

Integrated Fire Protective Coating System



Cafco FENDOLITE® MII

Integrated Fire Protective Coating System

INTRODUCTION

Cafco FENDOLITE® MII is a spray applied, single package factory controlled premix, based on vermiculite and Portland cement.

Cafco FENDOLITE® MII produces a monolithic coating able to withstand the thermal shocks experienced in a high intensity hydrocarbon fire. Concrete structures in particular, will be protected from explosive spalling when coated with Cafco FENDOLITE® MII.

Although low in density, thus significantly reducing dead load, Cafco FENDOLITE® MII is highly durable and will not crack or spall under mechanical impact.

Cafco FENDOLITE® MII is used for application on construction elements such as individual steel or concrete sections particularly where off-site application is required. It is also suitable for use on structures and vessels in the oil, gas, petrochemical and power industries.



Properties and performance	
Colour and finish	Off-white, monolithic, spray texture. May be floated or roller finished.
Theoretical coverage	62m ² /tonne at 25mm thickness
Cure	By hydraulic set
Initial set	2 to 6 hours at 20°C and 50% RH
Density	Minimum 775kg/m ³ ± 15% (when dry and in place)
Combustibility	Non-combustible to Euroclass A1 (EN 13501-1)
Smoke generation	Does not contribute to smoke generation
Thermal conductivity	0.19W/mK at 20°C
Corrosion resistance	Does not promote corrosion of steel. However, a primed substrate is recommended for long term corrosion resistance, particularly when the structure is to be fully exposed to the elements.
pH value	12.0-12.5
Sound absorption	Noise reduction coefficient (NRC) 0.35
Fire resistance	<p>Concrete and steel structures protected with Cafco FENDOLITE® MII have undergone fire resistance tests at approved independent laboratories to recognised standards throughout the world, including:</p> <ul style="list-style-type: none"> • Australia (AS1530: Part 4) • UK (BS476: Parts 20-21: 1987 Appendix D and Euroclass A1 – EN 13501-1) • Germany (DIN 4102) • International Standard ISO 834 • Italy (UNI 11076) • USA (ASTM E119, UL 263 and UL 1709 - Design No. XR719) <p>The fire resistance test results relate solely to the constructions tested and test conditions imposed. Promat provides computer based thickness calculations to meet specific fire resistance requirements on request.</p>

ADVANTAGES

- Proven fitness for worldwide purpose.
- Over 25 years service.
- Unrivalled track record.
- Unequaled knowledge and experience.
- Proven whole life value.
- Available worldwide, supplied and installed.

FIRE PROTECTION THICKNESS

Fire protection thickness requirements are often specified in the owner operator's engineering codes of practice. Alternatively, please consult Promat Technical Department.

QUALITY ASSURANCE

Promat operates a quality system in accordance with ISO 9001:2000 and has received full accreditation to these standards.

Operating to these standards means that all activities, which have a bearing upon quality, are set out in written procedures. Systematic and thorough checks are made on all materials and their usage. Test equipment is subjected to regular checks and is referred back to national standards.

The information given in this data sheet is based on actual tests and is believed to be typical of the product. No guarantee of results is implied however, since conditions of use are beyond our control.



Cafco FENDOLITE® MII

Integrated Fire Protective Coating System

Please consult your nearest Promat office for specific details pertaining to local conditions.

Preparation	
Typical substrates	Steel and concrete
Substrate preparation	The substrate shall be clean, dry and free from visible moisture (including condensation), concrete laitance, formwork release oils, loose mill scale, loose rust and any other condition preventing good adhesion. Concrete curing agents should not be used.
Mesh reinforcement	Most fire tests conducted have been carried out without mesh reinforcement, to demonstrate the ability of Cafco FENDOLITE® MII to stay in place under the most severe fire conditions. However, for maximum long term in-service durability, the use of lightweight mesh reinforcement is recommended for exterior work and for interior use where vibration or mechanical damage and the possibility of subsequent loss of adhesion exist.

Application	
Initial steps	Application of Cafco FENDOLITE® MII must be carried out by an applicator recognised by Promat.
Methods	Mix Cafco FENDOLITE® MII with potable water in a suitable mixer and apply by a spraying machine approved by Promat. Cafco FENDOLITE® MII may also be float or roller finished or left with a spray texture. A hand applied patching mix is available for minor repairs, i.e. Cafco FENDOLITE® TG.
Limitations	Cafco FENDOLITE® MII may be applied when the substrate and air temperatures are at least 2°C and rising, but should not be applied if the substrate or air temperatures are less than 4°C and falling. Maximum substrate and air temperature is 50°C. Substrate temperature should be at least 2°C above dew point temperature.

TOP COATING

Under certain circumstances, Cafco top coatings may be used as protection from frequent wash down, long term chemical spills, or for improved resistance to fungal, algae and bacterial growth. Please consult Promat for details.

PACKAGING

20kg bags.

STORAGE

Off the ground and kept dry until ready for use.

SHELF LIFE

Maximum 12 months.

ENVIRONMENTAL

- Do not discharge into drains, watercourses or soil.
- Not readily biodegradable.
- Not expected to bioaccumulate.
- Not expected to be toxic to aquatic life except at high concentrations.

HEALTH AND SAFETY

Adequate ventilation must be provided during use. Avoid contact with the skin and eyes by using eye protection, gloves, barrier cream and a face mask.

If the product comes into contact with the skin, wash immediately with soap and water. If the eyes are affected, flush with plenty of water and seek medical attention immediately.

A safety data sheet is available from Promat upon request.

Promat activities are conducted with due regard to all statutory requirements with appropriate safeguards against exposing employees and the public to health and safety risks.



For latest information of the Promat Asia Pacific organisation, please refer to www.promat-ap.com

ASIA PACIFIC HEADQUARTERS

Promat International (Asia Pacific) Ltd.
Unit 19-02-01, Level 2 PNB Damansara
No.19 Lorong Dungun, Damansara Heights
50490 Kuala Lumpur
MALAYSIA
Tel: +60 (3) 2095 5111
Fax: +60 (3) 2095 6111
Email: spraysinfo@promat-ap.com

AUSTRALIA

Promat Australia Pty. Ltd.
1 Scotland Road
Mile End South, SA 5031
Tel: 1800 PROMAT (776 628)
Fax: +61 (8) 8352 1014
Email: spraysinfo@promat.com.au

New South Wales Office **Promat Australia Pty. Ltd.**

Unit 1, 175 Briens Road
Northmead, NSW 2152
Tel: 1800 PROMAT (776 628)
Fax: +61 (2) 9630 0258
Email: spraysinfo@promat.com.au

Victoria Office

Promat Australia Pty. Ltd.
3/273 Williamstown Road
Port Melbourne, VIC 3207
Tel: 1800 PROMAT (776 628)
Fax: +61 (3) 9645 3844
Email: spraysinfo@promat.com.au

Queensland Office

Promat Australia Pty. Ltd.
Unit 2 Level 1
49 Gregory Tce
Spring Hill, QLD 4000
Tel: 1800 011 376
Fax: 1800 334 598
Email: spraysinfo@promat.com.au

CHINA

Promat China Ltd.
Room 503, Block B, Qi Lin Plaza
13-35 Pan Fu Road
510180 Guangzhou
Tel: +86 (20) 8136 1167
Fax: +86 (20) 8136 1372
Email: spraysinfo@promat-ap.com

Beijing Office

Promat North China
(Division of Promat China Ltd.)
Room 1507 Building 5, SOHO Xiandaicheng
No.88 Jianguo Road, Chaoyang District
100022 Beijing
Tel: +86 (10) 8589 1254
Fax: +86 (10) 8589 2904
Email: spraysinfo@promat-ap.com

For Promat International groups worldwide:
www.promat-international.com

1. This document is produced on the basis of information and experience available at the time of preparation. Promat is constantly reviewing and updating all of its test data and reserves the right to change products and specifications without notice.
2. Promat is not responsible if recipients of fire test reports, assessments or literature incorrectly interpret said contents and use products based on those interpretations.

HONG KONG

Promat International (Asia Pacific) Ltd.
Room 1010, C.C. Wu Building
302-308 Hennessy Road
Wanchai
Tel: +852 2836 3692
Fax: +852 2834 4313
Email: spraysinfo@promat-ap.com

INDIA

Promat International (Asia Pacific) Ltd.
(India Representative Office)
610-611, Ansal Imperial Tower
C-Block, Community Centre
Naraina Vihar, Naraina
110028 New Delhi
Tel: +91 (11) 2577 8413
Fax: +91 (11) 2577 8414
Email: spraysinfo@promat-ap.com

Bangalore Office

Promat International (Asia Pacific) Ltd.
(India Representative Office)
Cabin No.BC-9 & BC-10
Oculus Workspaces, No.66/1, 2nd Floor
Coles Road, Frazer Town
560005 Bangalore
Tel: +91 (80) 4031 4151
Fax: +91 (80) 4125 2135
Email: spraysinfo@promat-ap.com

Mumbai Office

Promat International (Asia Pacific) Ltd.
(India Representative Office)
Stylus Serviced Offices
Ground Floor, Velocity
Phase 1, Logitech Park
Andheri Kurla Road, Andheri East
400072 Mumbai
Tel: +91 (22) 6769 4567
Fax: +91 (22) 6769 4568
Email: spraysinfo@promat-ap.com

MALAYSIA

Promat (Malaysia) Sdn. Bhd.
Unit 19-02-01, Level 2 PNB Damansara
No.19 Lorong Dungun, Damansara Heights
50490 Kuala Lumpur
Tel: +60 (3) 2095 8555
Fax: +60 (3) 2095 2111
Email: spraysinfo@promat-ap.com

SINGAPORE

Promat Building System Pte. Ltd.
10 Science Park Road, #03-14 The Alpha,
Singapore Science Park II
Singapore 117684
Tel: +65 6776 7635
Fax: +65 6776 7624
Email: spraysinfo@promat-ap.com

Your local Promat supplier

